






linear dimension(Tolerances Standard GB/T 14486-2008)								—   		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60



PCB LAYOUT



REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
A	新发行		CLF	21.03

UL/CUL 技术 参数				
UL/CUL Technical Data				
等 级 Use Group		B	C	D
额定电压 Rated Voltage	[V]	300	-	300
额定电流 Rated Current	[A]	10	-	10
接线范围 Wire Range		26-16		
单/多芯线 Solid/Stranded	[AWG]			
耐电压 Withstanding Voltage		1600V/1Min		
IEC 技术参数				
IEC Technical Data				
过电压类别 Overvoltage Category		III	III	II
污染等级 Contamination Class		3	2	2
额定电压 Rated Voltage	[V]	160	200	400
额定电流 Rated Current	[A]	10	10	10
额定冲击电压 Impulse withstand voltagea	[KV]	2.5	2.5	2.5
导线截面积 Conductor cross section		1.0		
硬质/柔性导线 Solid/ flexible	[mm ²]			
材 料 Material				
绝缘材料 Insulation Material		PA66		
阻燃等级 Imflamability		UL94V-0		
导体材料 Contactor Material		铜合金 Copper alloy		
导体表面镀层 Contactive Coating		镀锡 Tin Plated		
一般参数 Other Data				
间距 Pitch	[mm]	3.5		
极数 Poles	[P]	2-24		
剥线长度 Stripping Length	[mm]	6		
螺丝 Screw/扭矩 Torque(Max)	[N.m]	M2.0/0.2		
工作温度 Operating temperatur	[°C]	-40~+105		
引针尺寸 Pin Dimensions	[mm]	3.5		
PCB板孔径 PCB Hole Diameter	[mm]	1.3		

DES.	LQQ	DATE	21.03.13	单位 / UNITS	mm	尺寸 / SIZE	A4	比例 / SCALE	1:1	第三视角 / THIRD ANGLE PROJECTION		版本 /	A
CHK.	SY	DATE	21.03.13	SHANGHAI SHANYE ELECTRONICS CO.,LTD								REV	
APP.	CLF	DATE	21.03.13							名称 /	127S-3.5		
				TITLE									